



FLEISCHHACKER

FOR THOSE ON A BUDGET –
Available straight from stock!

Orbital Vortex Mixer

with standard holder for individual test tubes

Model	MX-S	MX-F
Shaking mode	Orbital	
Orbital diameter	4 mm	
Motor input	58 W	
Motor output	10 W	
Speed range	0~2500 rpm	2500 rpm
Speed display	Scale	/
Operating mode	Continuous/momentary operation	
Ambient temperature	5 – 40 °C	
Relative humidity	80%	
Protection rating	IP21	
Power consumption	60 W	
Power supply	AC 110/220 V 50/60 Hz	
Standard accessories	VT1.1 Standard attachment	
External dimensions in mm (W x D x H)	127 x 160 x 130	
Total weight	3 kg	



Orbital Vortex Mixer MX-F
Item no.: 17725737

Orbital Vortex Mixer MX-S
Item no.: 7314707

Magnetic stirrer

with aluminium or ceramic plate

Model	BS-2H	BS-4H
Plate dimensions in mm	120 x 120	190 x 190
Material	Cast aluminium with surface coating	Ceramic
Speed range	100–2000 rpm	200–2000 rpm
Heating temperature	380 °C	350 °C
Power consumption	180 W	350 W
Power supply	110/240 V, 50/60 Hz	110/240 V, 50/60 Hz
Standard accessories	Adjustable stand, stirring rod	
External dimensions in mm (W x D x H)	200 x 120 x 90	265 x 185 x 190
Total weight	3 kg	3.4 kg



Magnetrührer BS-4H
Item no.: 17725738

BS-2H Magnetic Stirrer
Item no.: 17725736